

Bagging Machine PACKMAT TYP HV

Features

- ▶ Vertical bagging machine
- ▶ Application: Packaging of individual parts or bulk goods
- ▶ Consumable material: half tubular film (PE, PP, composite film)
- ▶ Sealing systems: digitally controlled
- ▶ Mobile machine frame
- ▶ Electric controls: VIPA 300 SPEED 7 or SIEMENS S7-300
- ▶ Operating unit: SIEMENS, touch panel colored display
- ▶ 3 password levels for access rights
- ▶ Software with graphical input masks
- ▶ Error messages in plain text
 - ▶ Menu management of the machine parameters
 - ▶ Data communication: Ethernet interface
 - ▶ Simple synchronization with additional machines
- ▶ Design according to:
 - ▶ DIN EN 60204-1 (VDE113-1/A1:2009-10)
 - ▶ Machinery Directives 2006/42/EC
 - ▶ Customer factory standards (on request)
- ▶ High level of maintenance and service friendliness

Options

- ▶ Manual infeed:
 - ▶ Hand-Working-Table, Counting-Weighing Table
- ▶ Automatic infeed:
 - ▶ Counting-, Weighing-, Assembly-machines
 - ▶ Thermo-transfer-Direct-Printer, Label applicator
 - ▶ Linked bag chain
 - ▶ Longitudinal- and transversal perforation device
 - ▶ Clean room design
 - ▶ Euro hole punch unit
 - ▶ Minigrip
 - ▶ Other options on request



Technical Data

Cycle speed: up to 50 Bags/min
(depending on bag length, product weight, infeed rate and options)

Bag width: to 280, 350, 450 mm
(dependent Machine type)

Bag length: dependent machine type,
directly adjustable

Passage clearance: up to 90, 130, 180 mm
(Special measure on request)

Film thickness: 40 – 180 µm

Electric supply: Project Dependent

Compressed Air: min. 5 bar (oil-free)

Dimension: for H280V 1400 x 900 x 1800 mm (L x W x H)

Weight: for H280V 200 kg